



# QuakeBond™ 401HCR Part A (Resin)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 1: Identification

#### 1.1. Identification

Trade name : QuakeBond™ 401HCR Part A (Resin)  
Product code : 20072

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

QuakeWrap, Inc  
6840 S Tucson Blvd  
Tucson, Arizona 85756 - USA  
T 520.791.7000 - F 520.791.0600  
[Office@quakewrap.com](mailto:Office@quakewrap.com) – [Quakewrap.com](http://Quakewrap.com)

#### 1.4. Emergency telephone number

Emergency number : Infotrac 800-535-5053

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Skin corrosion/irritation Category 2 H315  
Serious eye damage/eye irritation Category 2A H319  
Skin sensitization Category 1 H317

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) : Warning  
Hazard statements (GHS-US) : H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation

Precautionary statements (GHS-US) : P261 - Avoid breathing mist/vapors/spray  
P264 - Wash all contact areas thoroughly after handling  
P272 - Contaminated work clothing must not be allowed out of the workplace  
P280 - Wear protective gloves/protective clothing/eye protection  
P302+P352 - If on skin: Wash with plenty of mild soap and water  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P321 - Specific treatment: See SDS Section 4.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P501 - Dispose of contents/container to special waste facility in accordance with regional/national regulations

\*Specific component identification and/or percentages may be withheld as Trade Secret

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

# QuakeBond™ 401HCR Part A (Resin)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

| Name             | Product identifier  | %     | GHS-US classification   |
|------------------|---------------------|-------|---|
| Epoxy Resin      | (CAS No) 28064-14-4 | >= 50 | Skin Irrit. 2, H315<br>Eye Irrit. 2A, H319<br>Skin Sens. 1B, H317 |
| Titanium dioxide | (CAS No) 13463-67-7 | < 50  | Not classified  |

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention.
- First-aid measures after skin contact : Dispose of contaminated leather articles. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash clothing frequently. Keep work clothing separately. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
- First-aid measures after ingestion : Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Symptoms may be delayed.
- Symptoms/injuries after inhalation : Not expected to present a respiratory hazard under ambient conditions of normal industrial use due to low vapor pressure. Inhalation of vapors may cause respiratory irritation.
- Symptoms/injuries after skin contact : Causes skin irritation. May cause an allergic skin reaction. May cause sensitization by skin contact. Repeated or prolonged contact may cause injury to skin.
- Symptoms/injuries after eye contact : Causes serious eye irritation. Inflammation/damage of the eye tissue. Swelling and conjunctivitis.
- Symptoms/injuries after ingestion : May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Irritating and/or toxic gases or fumes likely if involved in fire or exposed to extreme heat.
- Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
- Other information : On burning: release of harmful/irritant gases/vapors.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses. Protective goggles.
- Emergency procedures : Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

- Protective equipment : Impermeable boots and protective equipment. Protective gloves. Safety glasses.
- Emergency procedures : Stop leak if safe to do so. Prevent product from entering drains.

#### 6.2. Environmental precautions

Avoid release to the environment.

# QuakeBond™ 401HCR Part A (Resin)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.3. Methods and material for containment and cleaning up

Other information : Dispose of materials or residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : When heated, material emits irritating fumes.  
Precautions for safe handling : Avoid contact with skin and eyes. Wear personal protective equipment. Avoid contact with eyes.  
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a dry place.  
Maximum storage period : 12 months  
Storage temperature : 15 - 50 °C

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| Epoxy Resin (28064-14-4)      |                                     |                      |
|-------------------------------|-------------------------------------|----------------------|
| Not applicable                |                                     |                      |
| Titanium dioxide (13463-67-7) |                                     |                      |
| ACGIH                         | ACGIH TWA (mg/m <sup>3</sup> )      | 10 mg/m <sup>3</sup> |
| ACGIH                         | Remark (ACGIH)                      | LRT irr; A3          |
| OSHA                          | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 15 mg/m <sup>3</sup> |

### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Materials for protective clothing : butyl rubber. chloroprene rubber. nitrile rubber.  
Hand protection : Protective gloves.  
Eye protection : Safety glasses.  
Skin and body protection : Wear suitable protective clothing.  
Thermal hazard protection : Use insulated gloves when handling this material hot.  
Environmental exposure controls : Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Color : Gray  
Odor : Mild nondescript  
Odor threshold : No data available  
pH : No data available  
Melting point : Not applicable  
Freezing point : < 0 °C  
Boiling point : No data available  
Flash point : > 100 °C  
Relative evaporation rate (butyl acetate=1) : No data available  
Flammability (solid, gas) : No data available  
Explosion limits : No data available  
Explosive properties : No data available  
Oxidizing properties : No data available

# QuakeBond™ 401HCR Part A (Resin)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                                 |                     |
|---------------------------------|---------------------|
| Vapor pressure                  | : No data available |
| Relative density                | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Specific gravity / density      | : 1.25              |
| Solubility                      | : No data available |
| Log Pow                         | : No data available |
| Auto-ignition temperature       | : No data available |
| Decomposition temperature       | : No data available |
| Viscosity                       | : No data available |
| Viscosity, dynamic              | : 13000 cP          |

### 9.2. Other information

Minimum ignition energy : <

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reaction with amines in large amounts or under uncontrolled conditions may produce extreme heat with noxious smoke and fumes.

### 10.4. Conditions to avoid

Overheating.

### 10.5. Incompatible materials

Oxidizing agent.

### 10.6. Hazardous decomposition products

carbon oxides (CO and CO<sub>2</sub>). Residual monomer.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

| Titanium dioxide (13463-67-7) |               |
|-------------------------------|---------------|
| LD50 oral rat                 | > 5000 mg/kg  |
| LD50 dermal rabbit            | > 10000 mg/kg |
| LC50 inhalation rat (mg/l)    | > 6.8 mg/l/4h |

|                                   |  |
|-----------------------------------|--|
| Skin corrosion/irritation         | : Causes skin irritation.              |
| Serious eye damage/irritation     | : Causes serious eye irritation.       |
| Respiratory or skin sensitization | : May cause an allergic skin reaction. |
| Germ cell mutagenicity            | : Not classified                       |
| Carcinogenicity                   | : Not classified                       |

| Titanium dioxide (13463-67-7) |                                      |
|-------------------------------|--------------------------------------|
| IARC group                    | 2B - Possibly carcinogenic to humans |

|  |  |
|--|--|
| Reproductive toxicity                              | : Not classified   |
| Specific target organ toxicity (single exposure)   | : Not classified   |
| Specific target organ toxicity (repeated exposure) | : Not classified   |
| Aspiration hazard                                  | : Not classified   |
| Symptoms/injuries after inhalation                 | : Not expected to present a respiratory hazard under ambient conditions of normal industrial use due to low vapor pressure. Inhalation of vapors may cause respiratory irritation. |

# QuakeBond™ 401HCR Part A (Resin)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Symptoms/injuries after skin contact : Causes skin irritation. May cause an allergic skin reaction. May cause sensitization by skin contact. Repeated or prolonged contact may cause injury to skin.
- Symptoms/injuries after eye contact : Causes serious eye irritation. Inflammation/damage of the eye tissue. Swelling and conjunctivitis.
- Symptoms/injuries after ingestion : May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

### SECTION 12: Ecological information

#### 12.1. Toxicity

- Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

| Titanium dioxide (13463-67-7) |  |
|-------------------------------|--|
| LC50 fish 1                   | > 1000 mg/l Pimephales promelas (fathead minnow)   |
| EC50 Daphnia 1                | > 1000 mg/l Daphnia magna (Water flea)   |
| ErC50 (algae)                 | > 100 mg/l Pseudokirchneriella subcapitata (green algae)   |
| Threshold limit algae 1       | 61 mg/l (EC50; Other; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value) |

#### 12.2. Persistence and degradability

| Epoxy Resin (28064-14-4)        |   |
|---------------------------------|---|
| Persistence and degradability   | Biodegradability in soil: no data available.                          |
| Titanium dioxide (13463-67-7)   |   |
| Persistence and degradability   | Biodegradability: not applicable. Low potential for mobility in soil. |
| Biochemical oxygen demand (BOD) | Not applicable  |
| Chemical oxygen demand (COD)    | Not applicable  |
| ThOD                            | Not applicable  |

#### 12.3. Bioaccumulative potential

| Epoxy Resin (28064-14-4)      |                                    |
|-------------------------------|------------------------------------|
| Log Pow                       | 3                                  |
| Bioaccumulative potential     | No bioaccumulation data available. |
| Titanium dioxide (13463-67-7) |                                    |
| Bioaccumulative potential     | Not bioaccumulative.               |

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

- Waste treatment methods : Landfilling of free liquid not recommended. Fuels burning or incineration preferred for material disposed of in "as sold" condition if regulations permit.
- Waste disposal recommendations : Collect all waste in suitable and labeled containers and dispose according to local legislation.
- Additional information : Industrial waste. Landfilling of free liquid not recommended. Fuels burning or incineration preferred for material disposed of in "as sold" condition if regulations permit.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Not regulated for transport

#### TDG

No additional information available

# QuakeBond™ 401HCR Part A (Resin)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Transport by sea

Not regulated for transport

### Air transport

Not regulated for transport

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

|   |  |
|---|--|
| <b>efi Polymers Chemical Resistant Epoxy Resin 20072 / Quakewrap 401HCR Chemical Resistant Coating Resin Part A</b> |  |
| SARA Section 311/312 Hazard Classes   | Immediate (acute) health hazard  |
| <b>Epoxy Resin (28064-14-4)</b>   |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory   |  |
| EPA TSCA Regulatory Flag  | XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)) |
| SARA Section 311/312 Hazard Classes   | Immediate (acute) health hazard  |
| <b>Titanium dioxide (13463-67-7)</b>  |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory   |  |

### 15.2. International regulations

#### CANADA

|   |   |
|---|---|
| <b>efi Polymers Chemical Resistant Epoxy Resin 20072 / Quakewrap 401HCR Chemical Resistant Coating Resin Part A</b> |   |
| WHMIS Classification  | Class D Division 2 Subdivision B - Toxic material causing other toxic effects |

#### EU-Regulations

No additional information available

#### National regulations

|   |  |
|---|--|
| <b>efi Polymers Chemical Resistant Epoxy Resin 20072 / Quakewrap 401HCR Chemical Resistant Coating Resin Part A</b>                         |  |
| All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory |  |
| <b>Titanium dioxide (13463-67-7)</b>  |  |
| Listed on IARC (International Agency for Research on Cancer)  |  |

### 15.3. US State regulations

|  |  |
|--|--|
| <b>Titanium dioxide (13463-67-7)</b>                       |  |
| U.S. - New Jersey - Right to Know Hazardous Substance List |  |

## SECTION 16: Other information

#### Abbreviations and acronyms

: N.A. - Not Applicable  
N.E. - Not Established  
N.D. - Not Determined  
ACGIH = American Conference of Governmental Industrial Hygienists  
OSHA = US Occupational Health and Safety Administration  
TLV-TWA = Threshold Limit Value-Time Weighted Average (8 hrs)  
STEL = Short-Term Exposure Limit (15 min)  
C = Ceiling Value  
PEL = Permissible Exposure Limit  
OEL = Occupational Exposure Limit  
IDLH = Immediately Dangerous to Life and Health  
ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
PNEC = Predicted No Effect Concentration  
LOAEL = Lowest Observed Adverse Effect Level  
NOAEL = No Observed Adverse Effect Level  
NOAEC = No Observed Adverse Effect Concentration.

# QuakeBond™ 401HCR Part A (Resin)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Other information

: **DISCLAIMER:** To the best of our knowledge, the information contained in this MSDS is accurate or is obtained from sources believed to be accurate. However, no liability, expressed or implied, is assumed for the accuracy or completeness of the information contained herein. Buyer assumes liability in its use of the material.

### Full text of H-phrases:

|      |                                     |
|------|-------------------------------------|
| H315 | Causes skin irritation              |
| H317 | May cause an allergic skin reaction |
| H319 | Causes serious eye irritation       |

### NFPA health hazard


: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

### NFPA fire hazard

: 1 - Must be preheated before ignition can occur.

### NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

#### Health

: 2 Moderate Hazard - Temporary or minor injury may occur

#### Flammability

: 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

#### Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

### Personal protection

: C

C - Safety glasses, Gloves, Synthetic apron

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*